

Oven Cabinet Conversion Instructions

Remember to measure twice and cut once!

Cabinet	Doors
Single Oven Opening	
Mullion A	Drawer 1
Mullion B	Drawer 2
Mullion C	Drawer 3

Single Oven- Leave as is.

Cutting Mullions: Be sure to cut the mullion at the edge of the frame of the cabinet. DO NOT CUT THE FRAME.

Double Oven- Remove Mullion A and B. Use Shims to help adjust ovens.

Single Oven with Microwave- It's important to dry fit your oven first. Then measure the microwave.

You have varying options depending on the microwave. The best option is to leave Mullion A in place and remove Mullion B. Then insert the microwave in the drawer space for Drawer 1 and 2. Use the removed mullions to fill in space if needed. If necessary, you can remove Mullion A, however, it is not recommended unless using the double oven option. Use Shims to help adjust for leveling.

NOTE: If you have a small microwave, removing Mullion B and Drawer 1 may be all the space you need. You can always remove the drawer face from Drawer 2 and adhere it to the cabinet for aesthetic purposes, although non functional.

Warming Drawer- Drawer 3 is specially designed width, height and depth for a warming drawer.

Special Note: All measurements for the Oven Cabinet were taken at Sears®, due to the large variety of appliances available. All fits are for standard size appliances.



www.peakhomeproducts.com